

DESCRIPTION OF THE PRODUCT

Mixture of high quality polymers in water dispersion.

FIELDS OF USE

The product, due to its viscosity, allows the protection and the waterproofing of vertical grouts, also in the presence of micro-lesions, preventing the penetration of rain.

The product is transparent, and it doesn't turn yellow even if it is exposed to U.V. rays.

SURFACE PREPARATION

Accurately clean the support to eliminate dust, crumbly parts, foreign or bonding-proof matters. Surface must be perfectly dry.

RECOMMENDATIONS

Do not add additives.

Do not add water and/or solvents.

Do not use should the container be damaged.

Protect for the first 24 hours from its application from water, rain, and snow.

Do not apply if night dampness is imminent.

Apply the product with a temperature included between + 5 ° C e + 35 ° C.

APPLICATION

The product is ready to be used and can be applied by brush on a clean, dry and exsiccated support.

CONSUMPTION

According to grouts' porosity.

PACKAGING

5 - 20 kg cans.

STORAGE

The product can be stored in its undamaged pack for 6 months. Keep in a dry and protected place, The product isn't frost-proof. Store at temperature included between +10°C e +30°C.

SAFETY INSTRUCTIONS

PRECAUTIONS

For information about safety, user must refer to the most recent Manufacturer Safety Data Sheet, edited in accordance with the regulations in place, which contains physical, toxic and other data about the product in use.

ECOLOGY

Do not dispose the product and/or empty containers in the environment. Consult the most recent Manufacturer Safety Data Sheet for further information about disposals.

PRODUCT FOR PROFESSIONAL USE

PRODUCT'S CHARACTERISTIC DATAS

Look	Liquid
Colour once it is dried up	Transparent
Dry residual (%)	35 ± 1
pH	7,5 - 9,5
Brookfield Viscosity at 20°C (Cps)	50 - 350

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.